

Application No.: 10/530,695
Preliminary Amendment dated: 2/1/2006

AMENDMENTS TO THE CLAIMS

1. – 43. (Cancelled)

44. (new) An apparatus, comprising:

at least one seismic sensor; and

a plurality of sources deployed in a manner structurally independent of the seismic sensors and adapted to provide a positioning signal distinguishable from a seismic survey signal to the seismic sensors concurrently with the seismic survey signal.

45. (new) The apparatus of claim 44, wherein the sources are adapted to provide the positioning signal at a frequency outside the bandwidth of the seismic survey signal.

46. (new) The apparatus of claim 45, wherein the sources are adapted to provide the positioning signal at a frequency above the bandwidth of the seismic survey signal.

47. (new) The apparatus of claim 46, wherein the sources are adapted to provide the positioning signal having a frequency bandwidth.

48. (new) The apparatus of claim 47, wherein the frequency bandwidth is approximately 700 Hz to 2000 Hz.

49. (new) The apparatus of claim 47, wherein the frequency bandwidth is approximately 1500 Hz to 4500 Hz.

50. (new) The apparatus of claim 44, wherein the plurality of sources comprises between two and five sources, inclusive.

51. (new) The apparatus of claim 50, wherein the plurality of sources comprises three sources.

Application No.: 10/530,695

Preliminary Amendment dated: 2/1/2006

52. (new) The apparatus of claim 44, wherein the plurality of sources are piezoelectric sources.
53. (new) The apparatus of claim 44, further comprising a signal processing unit adapted to determine the position of the seismic sensors from the received positioning signal.
54. (new) The apparatus of claim 53, wherein the signal processing unit is adapted to determine the position of the seismic sensors using a plurality of propagation times from the plurality of sources to the at least one seismic sensor.
55. (new) The apparatus of claim 54, wherein the signal processing unit is adapted to determine the position of the seismic sensors by triangulation using the plurality of propagation times from the plurality of sources to the at least one seismic sensor.
56. (new) An apparatus, comprising:
at least one seismic sensor deployed on a sea bed; and
a plurality of sources adapted to provide to the seismic sensors a positioning signal distinguishable from a seismic survey signal concurrently with the seismic survey signal.
57. (new) The apparatus of claim 56, wherein the sources are adapted to provide the positioning signal at a frequency outside the bandwidth of the seismic survey signal.
58. (new) The apparatus of claim 57, wherein the sources are adapted to provide the positioning signal at a frequency above the bandwidth of the seismic survey signal.
59. (new) The apparatus of claim 58, wherein the sources are adapted to provide the positioning signal having a frequency bandwidth.
60. (new) The apparatus of claim 59, wherein the frequency bandwidth range is approximately 700 Hz to 2000 Hz.

Application No.: 10/530,695

Preliminary Amendment dated: 2/1/2006

61. (new) The apparatus of claim 60, wherein the frequency bandwidth range is approximately 1500 Hz to 4500 Hz.
62. (new) A method for determining a position of at least one seismic sensor capable of receiving a seismic survey signal, comprising:
transmitting a plurality of positioning signals from a plurality of sources deployed in a manner that is structurally independent of the seismic sensors, the positioning signals being distinguishable from the seismic survey signal;
receiving the positioning signals at the seismic sensors concurrently with the seismic survey signal; and
determining the position of the seismic sensors from the received positioning signals.
63. (new) The method of claim 62, wherein transmitting the plurality of positioning signals comprises transmitting the positioning signals at a frequency outside the bandwidth of the seismic survey signal.
64. (new) The method of claim 63, wherein transmitting the plurality of positioning signals comprises transmitting the positioning signals at a frequency above the bandwidth of the seismic survey signal.
65. (new) The method of claim 62, wherein determining the position of the seismic sensors using the received signals comprises determining a plurality of propagation times from the sources to the seismic sensors using the received signals.
66. (new) The method of claim 65, wherein determining the position of the seismic sensors comprises determining the position of the seismic sensors using the plurality of propagation times.
67. (new) The method of claim 66, wherein determining the position of the seismic sensors using the plurality of propagation times comprises determining the position of the sensors by triangulation using the plurality of propagation times.

Application No.: 10/530,695
Preliminary Amendment dated: 2/1/2006

68. (new) A method, comprising:

transmitting a plurality of positioning signals from a plurality of sources, the positioning signals being distinguishable from the seismic survey signal;

receiving, concurrently with the seismic survey signal, the positioning signals at a plurality of seismic sensors deployed on a sea bed; and

determining the position of the seismic sensors from the received positioning signals.

69. (new) The method of claim 68, wherein transmitting the plurality of positioning signals comprises transmitting the positioning signals at a frequency outside the bandwidth of the seismic survey signal.

70. (new) The method of claim 69, wherein determining the position of the seismic sensors using the received signals comprises determining a plurality of propagation times from the sources to the seismic sensors using the received signals.

71. (new) A system, comprising:

a vessel;

a seismic cable having at least one seismic sensor capable of receiving a seismic survey signal concurrently with a positioning signal that is distinguishable from the seismic survey signal, wherein the seismic cable is deployed from the vessel;

a plurality of buoys;

a plurality of sources adapted to provide the positioning signal, at least one source being suspended beneath the survey vessel and the remainder being deployed on the buoys; and

a signal processing unit adapted to determine the position of the seismic sensors from the received positioning signals.

72. (new) The system of claim 71, wherein the buoys are autonomous self-propelled buoys.

73. (new) The system of claim 71, wherein the buoys are towed behind the survey vessel.

Application No.: 10/530,695
Preliminary Amendment dated: 2/1/2006

75. (new) A system, comprising:

at least one seismic sensor capable of receiving a seismic survey signal concurrently with a positioning signal that is distinguishable from the seismic survey signal;

a plurality of autonomous self-propelled buoys; and

a plurality of sources coupled to the self-propelled autonomous buoys, the sources being adapted to provide the positioning signal.

76. (new) The system of claim 75, wherein the sources are suspended beneath the autonomous self-propelled buoys.

77. (new) The system of claim 75, further comprising a signal processing unit adapted to determine the position of the seismic sensors using the received positioning signals.

78. (new) The system of claim 75, wherein the seismic sensors are deployed on a seismic cable coupled to the vessel.

79. (new) A system, comprising:

a first vessel;

a seismic cable having at least one seismic sensor capable of receiving a seismic survey signal concurrently with a positioning signal that is distinguishable from the seismic survey signal, wherein the seismic cable is deployed from the first vessel;

a second vessel;

a plurality of buoys;

a plurality of sources adapted to provide a positioning signal, at least one source being coupled to the first vessel, at least one source being coupled to the second vessel, and the remainder being deployed on the buoys; and

a signal processing unit adapted to determine the position of the seismic sensors from the received positioning signals.

80. (new) The system of claim 79, wherein at least a portion of the buoys are deployed along a length of the seismic cable.

Application No.: 10/530,695
Preliminary Amendment dated: 2/1/2006

81. (new) The system of claim 79, further comprising an array of seismic cables having at least one seismic sensor capable of receiving the seismic survey signal.

82. (new) The system of claim 81, wherein at least a portion of the buoys are deployed among the array of seismic cables.